# NSN 5930-01-056-4702

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-056-4702

### **Thread Length:**

0.230 inches single mounting facility and 0.255 inches single mounting facility

### **Overall Length:**

Between 1.834 inches and 1.869 inches

### First Flat Length:

0.235 inches single actuator and 0.265 inches single actuator

### Flat Height:

0.093 inches single actuator

#### **Shaft Diameter:**

0.123 inches single actuator and 0.120 inches single actuator

### **Shaft Length:**

0.625 inches single actuator

#### **Overall Diameter:**

Between 0.155 inches and 0.185 inches

### **Individual Section Quantity:**

1

# **Switch Contact Basic Design:**

Nonpile-up symmetrical

# **Pole Quantity:**

1 single section front

# **Throw Quantity:**

8 single section front

# **Mounting Method:**

Threaded bushing single mounting facility

### **Thread Size:**

0.250 inches single mounting facility

### **Contact Voltage Rating In Volts:**

28.0 dc at sea level

#### **Shaft Type:**

Round, flatted single actuator

# **Terminal Type:**

Tab, solder lug

### **Contact Switching Action:**

Makes before breaks single section front

### **Special Features:**

Pull to turn to enter or leave positions 1 and 8

# Style Designator:

Miniature, bushing mount

# **Test Data Document:**

98230-0n199316-2 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

### **Thread Series Designator:**

Unf single mounting facility

# NSN 5930-01-056-4702

Rotary Switch - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0