

View Online at <https://aerobasegroup.com/nsn/5930-01-056-4702>

**Thread Length:**

0.230 inches single mounting facility and 0.255 inches single mounting facility

**Overall Length:**

Between 1.834 inches and 1.869 inches

**First Flat Length:**

0.235 inches single actuator and 0.265 inches single actuator

**Flat Height:**

0.093 inches single actuator

**Shaft Diameter:**

0.123 inches single actuator and 0.120 inches single actuator

**Shaft Length:**

0.625 inches single actuator

**Overall Diameter:**

Between 0.155 inches and 0.185 inches

**Individual Section Quantity:**

1

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 single section front

**Throw Quantity:**

8 single section front

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.250 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Makes before breaks single section front

**Special Features:**

Pull to turn to enter or leave positions 1 and 8

**Style Designator:**

Miniature, bushing mount

**Test Data Document:**

98230-0n199316-2 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Thread Series Designator:**

Unf single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0