NSN 5930-01-056-6292

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-056-6292

view Online at https://aerobasegroup.com/hsh/5930-01-056-6292
Body Style:
Panel mounted
Hazardous Locations/environmental Protection:
Explosion proof and humidity resistant
Overall Length:
3.655 inches
Overall Height:
0.750 inches
Overall Width:
0.750 inches
Body Width:
0.750 inches
Body Height:
0.750 inches
Actuator Length:
0.530 inches
Actuator Style:
Rectangular
Actuator Height:
0.120 inches
Actuator Width:
0.530 inches
Actuator Color:
Black single actuator
Illuminated Actuator Color:
White single actuator
Actuator Inscription:
Valv single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Mounting Surface To Terminal End Distance:
3.535 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Full display lens
Nonpile-up Contact Arrangement:
3 pole, double throw, both positions maintained single switch unit
Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 500.000 milliamperes inductive dc and 1.000 amperes resistive ac and 500.000 milliamperes inductive ac

NSN 5930-01-056-6292

Push Switch - Page 2 of 2



Special	Features:
---------	-----------

Two 0.020 in. Wide white lines w/0.020 in. Diameter dots on a 36 line density pattern on right side of actuator

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0