

View Online at <https://aerobasegroup.com/nsn/5930-01-056-7290>

Thread Class:

2a all threaded stud

Thread Length:

0.390 inches single pressure connection

Overall Length:

2.280 inches

Outside Diameter:

0.125 inches single connection

Body Length:

1.571 inches

Overall Diameter:

Between 1.730 inches and 1.770 inches

Distance Between Mounting Facility Centers:

0.438 inches

Pressure Switch Type:

Gage

Width Across Flats:

1.125 inches

Operating Temperature Rating:

Between -55.0 degrees celsius and 71.0 degrees celsius

Mounting Method:

Inlet connection

Thready Qty Per Inch (tpi):

32 all threaded stud

Contact Action Stimulus:

Increase

Proof Pressure:

350.00 pounds per square inch gage

Thread Size:

0.125 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Threaded stud

Contact Load Current Rating:

2.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

62.50 actuation point pounds per square inch gage and 42.00 deactuation point pounds per square inch gage and 20.50 differential point pounds per square inch gage

Contact Voltage Rating In Volts:

24.0 dc at sea level single voltage

Pressure Connector Type:

Flared, threaded external single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0