## NSN 5930-01-057-2712

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-057-2712

O server Willelink (s
Overall Height:
0.500 inches
Body Diameter:
0.572 inches
Body Height:
0.315 inches
Unthreaded Mounting Hole Diameter:
0.115 inches
Distance Between Mounting Facility Centers:
0.812 inches
Tempurature Sensing Element Type:
Internal sensor
Operating Tempurature Rating:
Between -65.0 degrees fahrenheit and 450.0 degrees fahrenheit
Mounting Method:
Bracket and unthreaded hole
Features Provided:
Hermetically sealed case
Contact Action Stimulus:
Decrease
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, single throw, normally closed, momentary action
Terminal Type:
Tab, solder lug
Contact Load Current Rating:
5.0 amperes resistive load third voltage
Contact Adjustability:
Deactuation point not adjustable and actuation point not adjustable
Contact Stimulus Rating:
158.00 actuation point degrees fahrenheit and 138.00 deactuation point degrees fahrenheit
Contact Voltage Rating In Volts:
30.0 ac at sea level third voltage
Media For Which Designed:
Gas or liquid
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

## NSN 5930-01-057-2712

Thermostatic Switch - Page 2 of 2

**Fiig:** A048b0

