

View Online at <https://aerobasegroup.com/nsn/5930-01-057-2715>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof and shock proof

Overall Length:

0.781 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.500 inches

Overall Height:

0.619 inches

Overall Width:

0.250 inches

Body Length:

0.781 inches

Body Width:

0.250 inches

Body Height:

0.438 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.188 inches

Actuator Length:

0.125 inches

Actuator Style:

Rectangular

Actuator Height:

0.093 inches

Actuator Width:

0.125 inches

Actuator Free Position Height:

0.437 inches

Maximum Voltage Rating In Volts:

115.0 ac

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 two circuit, double break/double make, one position momentary single switch unit

Switch Release Force:

2.0 ounces

Switch Actuating Force:

Between 6.0 ounces and 10.0 ounces

Actuator Movement:

Between 0.050 pretravel inches and 0.012 overtravel inches and 0.020 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

500.000 milliamperes inductive ac

Special Features:

1 mtg slot 0.088 in. W by 0.100 in. Lg

Precious Material And Location:

Contact surfaces gold and contacts silver

Terminal Type And Quantity:

4 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0