NSN 5930-01-057-3813



Thermostatic Switch - Page 1 of 2	
View Online at https://aerobasegroup.com/nsn/5930-01-057-3813	
Thread Class:	
2b all threaded hole	
Overall Length:	
2.627 inches	
Overall Height:	
2.340 inches	
Overall Width:	
1.160 inches	
Body Length:	
Between 1.900 inches and 1.950 inches	
Body Width:	
1.160 inches	
Distance Between Mounting Facility Centers:	
1.937 inches	
Capillary Tube Length:	
Between 71.0 inches and 75.0 inches	
Bulb Length:	
Between 1.680 inches and 1.940 inches	
Bulb Diameter:	
0.125 inches	
Tempurature Sensing Element Type:	
Capillary tube-bulb	
Mounting Method:	
Bracket and threaded hole	
Thready Qty Per Inch (tpi):	
32 all threaded hole	
Contact Action Stimulus:	
Increase	
Thread Size:	
0.138 inches all threaded hole	
Mounting Facility Pattern:	
Two position in-line	
Nonpile-up Contact Arrangement:	
1 pole, single throw, normally open, momentary action	
Terminal Type:	
Threaded stud	
Contact Load Current Rating:	

5.0 amperes resistive load first voltage

Contact Adjustability:

Deactuation point adjustable, preset and actuation point adjustable, preset

Contact Adjustment Range:

+0.00/+26.00 actuation point degrees fahrenheit and +0.00/+26.00 deactuation point degrees fahrenheit

NSN 5930-01-057-3813

Thermostatic Switch - Page 2 of 2



Contact Ad	justment	Type:
------------	----------	-------

External deactuation point screw and external actuation point screw

Contact Stimulus Rating:

2.00 actuation point degrees fahrenheit and 18.00 deactuation point degrees fahrenheit

Contact Voltage Rating In Volts:

240.0 ac at sea level first voltage

Media For Which Designed:

Gas or liquid

Thread Series Designator:

Unc all threaded hole

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A048b0