## NSN 5930-01-057-6802

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-057-6802

Hazardous Locations/environmental Protection:
Watertight
Overall Length:
3.520 inches
Overall Height:
1.740 inches
Overall Width:
2.120 inches
Unthreaded Mounting Hole Diameter:
0.189 inches single mounting facility
Individual Section Quantity:
2
Knob Manufacturer Code:
27192
Knob Specificationial Markings:
Dw
Longest Horizontal Distance Between Mounting Centers:
1.620 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
1.250 inches single mounting facility
Switch Contact Basic Design:
Pile-up
Mounting Method:
Bracket single mounting facility and unthreaded hole single mounting facility
Features Provided:
Actuator knob
Pile-up Contact Form Arrangement:
1c each switch each section rear
Contact Voltage Rating In Volts:
440.0 highest ac voltage rating at sea level
Switch Actuator Momentary Position:
Counterclockwise single actuator and clockwise single actuator
Mounting Facility Pattern:
Four position rectangular single mounting facility
Switch Actuator Indexing Position Quantity:
4 single actuator
Terminal Type:
Tab w/screw
Contact Load Current Rating:
4.0 amperes resistive load highest dc voltage rating at sea level

**Style Designator:**Tap, circuit selector

## NSN 5930-01-057-6802

Rotary Switch - Page 2 of 2



C	ha	Ιf	1	ife	
•	ııe		_	.II C	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0