Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-057-6802

ew Online at https://defobasegroup.com/nai//3500-01-007-0002
azardous Locations/environmental Protection:
/atertight
verall Length:
.520 inches
verall Height:
740 inches
verall Width:
120 inches
nthreaded Mounting Hole Diameter:
189 inches single mounting facility
dividual Section Quantity:
nob Manufacturer Code:
7192
nob Specificationial Markings:
w
ongest Horizontal Distance Between Mounting Centers:
.620 inches single mounting facility
ongest Vertical Distance Between Mounting Centers:
250 inches single mounting facility
witch Contact Basic Design:
ile-up
lounting Method:
racket single mounting facility and unthreaded hole single mounting facil
eatures Provided:
ctuator knob
ile-up Contact Form Arrangement:
c each switch each section rear
ontact Voltage Rating In Volts:
40.0 highest ac voltage rating at sea level
witch Actuator Momentary Position:
ounterclockwise single actuator and clockwise single actuator
lounting Facility Pattern:
our position rectangular single mounting facility
witch Actuator Indexing Position Quantity:
single actuator
erminal Type:
ab w/screw
ontact Load Current Rating:
.0 amperes resistive load highest dc voltage rating at sea level
tyle Designator:
ap, circuit selector

## NSN 5930-01-057-6802

Rotary Switch - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A052b0

