NSN 5930-01-057-7645

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-057-7645

Thread Class:

3a single pressure connection

Thread Length:

0.550 inches single pressure connection

Hazardous Locations/environmental Protection:

Weatherproof

Overall Length:

3.000 inches

Overall Height:

1.000 inches

Overall Width:

1.000 inches

Pressure Switch Type:

Gage

Operating Tempurature Rating:

Between -40.0 degrees fahrenheit and 140.0 degrees fahrenheit

Mounting Method:

Outlet connection

Features Provided:

Electrical access port

Thready Qty Per Inch (tpi):

20 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

7500.00 pounds per square inch gage

Thread Size:

0.438 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Sensing Element Burst Pressure:

5500.00 pounds per square inch gage

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

7.0 amperes resistive load third voltage and 4.0 amperes inductive load third voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

500.00 actuation point pounds per square inch gage and 425.00 deactuation point pounds per square inch gage and 75.00 differential point

pounds per square inch gage

Contact Voltage Rating In Volts:

28.0 dc at sea level third voltage

NSN 5930-01-057-7645

Pressure Switch - Page 2 of 2



Pressure Connector Type:

Flared, threaded external single connection

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A048b0