

View Online at <https://aerobasegroup.com/nsn/5930-01-057-8267>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

0.515 inches

Overall Height:

1.190 inches

Overall Width:

Between 0.380 inches and 0.420 inches

Bushing Length:

0.330 inches

Body Length:

0.510 inches

Body Width:

0.290 inches

Body Height:

0.420 inches

Case Material:

Plastic

Actuator Style:

Round

Actuator Diameter:

0.110 inches

Actuator Height:

0.410 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained

Maximum Voltage Rating In Volts:

28.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 7.000 amperes resistive ac

Precious Material And Location:

Contact surfaces gold

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0