

View Online at <https://aerobasegroup.com/nsn/5930-01-057-8268>

**Body Style:**

Bushing mount

**Bushing Length:**

0.470 inches

**Body Length:**

1.312 inches

**Body Width:**

0.860 inches

**Case Material:**

Metal

**Actuator Style:**

Round

**Actuator Diameter:**

0.430 inches

**Actuator Height:**

1.180 inches

**Actuator Position-action Relationship:**

Up position momentary and down position maintained

**Actuator Position-locking Relationship:**

Up position locked in and down position locked in

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**End Application:**

An-ugc-129 19397

**Mounting Surface To Terminal End Distance:**

1.125 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

4 pole, double throw, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 3.000 amperes inductive dc and 2.400 amperes lamp dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac and 1.500 amperes lamp ac

**Test Data Document:**

81349-mil-s-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

UNF

**Terminal Type And Quantity:**

12 turret

**Specification Data:**

81349-mil-s-8805/92 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0