

View Online at <https://aerobasegroup.com/nsn/5930-01-057-8587>

Overall Length:

4.906 inches

Overall Height:

1.910 inches

Body Length:

3.625 inches

Unthreaded Mounting Hole Diameter:

0.257 inches

Longest Horizontal Distance Between Mounting Centers:

4.250 inches

Longest Vertical Distance Between Mounting Centers:

2.875 inches

Pressure Switch Type:

Gage

Operating Temperature Rating:

Between -62.0 degrees celsius and 75.0 degrees celsius

Mounting Method:

Flange and unthreaded hole

Features Provided:

Electrical access port

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position diagonal

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Tab w/screw

Contact Load Current Rating:

15.0 amperes resistive load second voltage

Contact Adjustability:

Actuation point adjustable, preset

Contact Adjustment Range:

+0.00/+100.00 actuation point pounds per square inch

Contact Adjustment Type:

Internal actuation point hex nut

Contact Stimulus Rating:

31.00 actuation point pounds per square inch and 26.00 deactuation point pounds per square inch

Contact Voltage Rating In Volts:

230.0 ac at sea level second voltage

Special Features:

Altered nameplate iaw ibm dwg 6935397

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0