NSN 5930-01-058-0864

Sensitive Switch - Page 1 of 2

Body Style:
Hole mounted
Overall Length:
0.781 inches



View Online at https://aerobasegroup.com/nsn/5930-01-058-0864

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.375 inches
Overall Width:
0.250 inches
Body Length:
0.781 inches
Body Width:
0.250 inches
Body Height:
0.356 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
0.088 inches
Actuator Style:
Round
Actuator Diameter:
0.092 inches
Actuator Free Position Height:
0.302 inches
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
End Application:
Ship, ohio class ssn (trident)
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
1.0 ounces
Criticality Code Justification:
Feat
Switch Actuating Force:
3.0 ounces
Actuator Movement:

Between 0.030 pretravel inches and 0.005 overtravel inches and 0.004 differential inches

NSN 5930-01-058-0864

Sensitive Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc and 2.500 amperes inductive dc and 2.000 amperes lamp dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac and 1.500 amperes lamp ac

Weapon system essential

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0