NSN 5930-01-058-7704

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-058-7704

Thread Class:

2a single threaded bushing

Thread Length:

0.187 inches single threaded bushing

Overall Height:

0.867 inches

Body Height:

0.437 inches

Overall Diameter:

Between 0.540 inches and 0.640 inches

End Application:

Air cb inst 94987

Tempurature Sensing Element Type:

Internal sensor

Operating Tempurature Rating:

Between -65.0 degrees fahrenheit and 500.0 degrees fahrenheit

Mounting Method:

Threaded bushing

Features Provided:

Hermetically sealed case

Thready Qty Per Inch (tpi):

32 single threaded bushing

Contact Action Stimulus:

Decrease

Thread Size:

0.138 inches single threaded bushing

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

5.0 amperes resistive load third voltage and 2.5 amperes inductive load third voltage and 1.0 amperes lamp load third voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

230.00 actuation point degrees fahrenheit and 240.00 deactuation point degrees fahrenheit

Contact Voltage Rating In Volts:

28.0 dc at sea level second voltage

Frequency In Hertz:

60.0 first voltage

Media For Which Designed:

Gas or liquid

NSN 5930-01-058-7704

Thermostatic Switch - Page 2 of 2

Style Designator:

A048b0



Disc
Test Data Document:
81349-mil-s-24236 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unc single threaded bushing
Specification Data:
81349-mil-s-24236/1 government specification
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig: