

View Online at <https://aerobasegroup.com/nsn/5930-01-058-7709>

Thread Class:

2b single mounting facility

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

6.062 inches

Overall Height:

5.062 inches

Overall Width:

4.562 inches

Shaft Diameter:

0.500 inches single actuator

Shaft Length:

1.500 inches single actuator

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

4.156 inches single mounting facility

Shortest Horizontal Distance Between Mounting Centers:

2.203 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

4.625 inches single mounting facility

End Application:

Sslv-38 02295

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Bracket single mounting facility and threaded hole single mounting facility

Thread Size:

0.190 inches single mounting facility

Contact Voltage Rating In Volts:

600.0 highest ac voltage rating at sea level

Switch Actuator Momentary Position:

Counterclockwise single actuator

Mounting Facility Pattern:

Isosceles triangle single mounting facility

Cam Actuated Switch Contact Arrangement:

2 pole, single throw, normally open, momentary action single switch single section periphery

Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Screw

Contact Load Current Rating:

5.0 amperes resistive load highest ac voltage rating at sea level

Style Designator:

Tap, circuit selector

Thread Series Designator:

Unf single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0