

View Online at <https://aerobasegroup.com/nsn/5930-01-059-0352>

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

4.375 inches

Overall Height:

6.188 inches

Overall Width:

3.188 inches

Pressure Switch Type:

Gage

Mounting Method:

Input port

Features Provided:

Electrical access port

Contact Action Stimulus:

Increase

Proof Pressure:

1000.00 pounds per square inch

Thread Size:

0.250 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Wire lead

Contact Load Current Rating:

300.0 milliamperes resistive load second voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+1.00/+75.00 actuation point pounds per square inch and +0.50/+73.50 deactuation point pounds per square inch

Contact Adjustment Type:

Internal deactuation point screw and internal actuation point screw

Contact Voltage Rating In Volts:

480.0 ac at sea level first voltage

Pressure Connector Type:

Gasket seal, threaded internal single connection

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0