## NSN 5930-01-059-2674

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-059-2674

Thread Le	ngth:
-----------	-------

0.375 inches single mounting facility

**Overall Height:** 

1.469 inches

**Overall Width:** 

1.312 inches

First Flat Length:

0.400 inches single actuator

Flat Height:

0.190 inches single actuator

**Shaft Diameter:** 

0.250 inches single actuator

**Shaft Length:** 

0.840 inches single actuator

**Nonturn Device Radius:** 

0.437 inches at 9: 00 o'clock

**Individual Section Quantity:** 

2

**Nonturn Device Type:** 

Tab at 9: 00 o'clock

**Switch Contact Basic Design:** 

Nonpile-up symmetrical

**Pole Quantity:** 

1 each section rear

**Throw Quantity:** 

4 each section rear

**Mounting Method:** 

Threaded bushing single mounting facility

**Contact Voltage Rating In Volts:** 

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:** 

11 single actuator

**Shaft Type:** 

Round, flatted single actuator

Terminal Type:

Tab, solder lug

**Contact Switching Action:** 

Breaks before makes each section rear

**Switch Actuator Positioning Increment:** 

30.0 degrees single actuator

**Switch Actuator Stop Device Type:** 

Adjustable stop single actuator

## NSN 5930-01-059-2674

Rotary Switch - Page 2 of 2



Contact	Load	Current	Rating:
---------	------	---------	---------

1.5 amperes resistive load ac at sea level

**Style Designator:** 

Circular wafer, bushing mount

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0