

View Online at <https://aerobasegroup.com/nsn/5930-01-059-5580>

Overall Length:

3.520 inches

Overall Height:

1.770 inches

Overall Width:

0.980 inches

Unthreaded Mounting Hole Diameter:

0.100 inches single mounting facility

Individual Section Quantity:

3

Longest Horizontal Distance Between Mounting Centers:

3.354 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

0.900 inches single mounting facility

Mounting Method:

Bracket single mounting facility and unthreaded hole single mounting facility

Actuator Type:

Thumbwheel all actuators

Contact Voltage Rating In Volts:

28.0 ac at sea level 28.0 dc at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

8 1st actuator 10 2nd actuator 10 3rd actuator

Terminal Type:

Printed circuit

Contact Load Current Rating:

125.0 milliamperes resistive load ac at sea level 125.0 milliamperes resistive load dc at sea level

Readout Indicator Marking:

0, 1, 2, 3, 4, 5, 6, 7, 8 1st section 0, 1, 2, 3, 4, 5, 6, 7, 8, 9 2nd section 0, 1, 2, 3, 4, 5, 6, 7, 8, 9 3rd section

Contact Arrangement Truth Table:

bcd, 1 pole - 8 positions 1st section bcd complement only, 1 pole - 10 positions 2nd section bcd complement only, 1 pole - 10 positions 3rd section

Color:

Black each body black each indicator background white each indicator marking white each lamp

Precious Material And Location:

Contact and printed circuit board circuit surfaces gold

Precious Material:

Gold

Style Designator:

Rectangular inline indicating

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0