NSN 5930-01-059-6537

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-059-6537

3
Hazardous Locations/environmental Protection:
Moisture resistant and salt spray resistant and vibration resistant
Overall Length:
2.500 inches
Body Length:
1.770 inches
Overall Diameter:
1.120 inches
Pressure Switch Type:
Absolute
Operating Tempurature Rating:
Between -55.0 degrees celsius and 85.0 degrees celsius
Mounting Method:
Threaded bushing
Features Provided:
Hermetically sealed case
Thready Qty Per Inch (tpi):
27 single threaded bushing
Contact Action Stimulus:
Decrease
Proof Pressure:
60.00 pounds per square inch absolute
Thread Size:
0.125 inches single threaded bushing
Nonpile-up Contact Arrangement:
1 pole, single throw, normally closed, momentary action
Terminal Type:
Tab, solder lug
Contact Load Current Rating:
5.0 amperes resistive load single voltage and 2.0 amperes inductive load single voltage
Contact Adjustability:
Actuation point not adjustable
Contact Stimulus Rating:
27.50 actuation point pounds per square inch absolute
Contact Voltage Rating In Volts:
28.0 dc at sea level single voltage
Media For Which Designed:
Gas
Style Designator:
Cylindrical

Cylindrical

Thread Series Designator:

Npt single threaded bushing

NSN 5930-01-059-6537

Pressure Switch - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0