

View Online at <https://aerobasegroup.com/nsn/5930-01-060-9874>

**Body Style:**

Printed circuit

**Hazardous Locations/environmental Protection:**

Dustproof and vibration resistant and shock resistant

**Overall Length:**

Between 0.470 inches and 0.490 inches

**Overall Height:**

Between 0.578 inches and 0.628 inches

**Overall Width:**

Between 0.370 inches and 0.390 inches

**Body Length:**

Between 0.470 inches and 0.490 inches

**Body Width:**

Between 0.370 inches and 0.390 inches

**Body Height:**

Between 0.237 inches and 0.257 inches

**Case Material:**

Plastic

**Switch Actuator Quantity:**

4

**Actuator Style:**

Rectangular

**Actuator Height:**

Between 0.195 inches and 0.205 inches

**Actuator Width:**

0.070 inches

**Actuator Position-action Relationship:**

Up position maintained and down position maintained

**Maximum Voltage Rating In Volts:**

30.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Printed circuit

**Nonpile-up Contact Arrangement:**

1 pole, double throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

125.0 milliamperes resistive dc

**Precious Material And Location:**

Contact surfaces gold

**Terminal Type And Quantity:**

8 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0