## NSN 5930-01-061-5874

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-061-5874 **Thread Class:** 2a single mounting facility Thread Length: 0.469 inches single mounting facility **Hazardous Locations/environmental Protection:** Dustproof **Overall Length:** 3.719 inches First Flat Length: 0.750 inches single actuator **Shaft Diameter:** 0.250 inches single actuator **Shaft Length:** 1.438 inches single actuator **Overall Diameter:** 2.000 inches **Individual Section Quantity: Knob Manufacturer Code:** 82121 **Knob Specificationial Markings:** Arrow **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 2 each section rear **Throw Quantity:** 2 each section rear **Mounting Method:** Threaded bushing single mounting facility **Features Provided:** Actuator knob

Thready Qty Per Inch (tpi):

32 single mounting facility

**Thread Size:** 

0.469 inches single mounting facility

**Contact Voltage Rating In Volts:** 

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:** 

2 single actuator

**Shaft Type:** 

Round, hollowed, flatted single actuator

## **NSN 5930-01-061-5874**Rotary Switch - Page 2 of 2



Criticality Code Justification:
Feat
Terminal Type:
Tab w/screw
Contact Switching Action:
Breaks before makes each section rear
Switch Actuator Positioning Increment:
45.0 degrees single actuator
Switch Actuator Stop Device Type:
Fixed stop single actuator
Contact Load Current Rating:
5.0 amperes resistive load dc at sea level
Special Features:
Item must comply with requirements of desc production standard no. L02439; for navy nuclear propulsion plant products only
Precious Material And Location:
Contact surfaces silver
Precious Material:
Silver
Style Designator:
Tap, circular, bushing mount
Thread Series Designator:
Uns single mounting facility
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Filig:
A052b0