

View Online at <https://aerobasegroup.com/nsn/5930-01-061-5877>

Thread Class:

2b 2nd mounting facility

Thread Length:

0.438 inches 1st mounting facility

Overall Length:

4.376 inches

Overall Height:

2.500 inches

First Flat Length:

0.750 inches single actuator

Flat Height:

0.219 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

1.188 inches single actuator

Individual Section Quantity:

4

Knob Manufacturer Code:

82121

Knob Manufacturer Part Number:

A

Knob Specification Markings:

Arrow

Longest Horizontal Distance Between Mounting Centers:

1.641 inches 2nd mounting facility

Longest Vertical Distance Between Mounting Centers:

1.641 inches 2nd mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section front

Throw Quantity:

3 each section rear

Mounting Method:

Threaded bushing w/panel seal 1st mounting facility

Features Provided:

Actuator knob

Thready Qty Per Inch (tpi):

32 1st mounting facility

Thread Size:

0.469 inches 1st mounting facility

Contact Voltage Rating In Volts:

125.0 ac at sea level

Switch Actuator Momentary Position:

Clockwise single actuator and counterclockwise single actuator

Rotor Through Connection Quantity:

1 each section

Mounting Facility Pattern:

Four position rectangular 2nd mounting facility

Switch Actuator Indexing Position Quantity:

3 single actuator

Shaft Type:

Round, flatted, threaded hole single actuator

Criticality Code Justification:

Feat

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

10.0 amperes resistive load ac at sea level

Special Features:

Weapon system

Style Designator:

Tap, circuit selector

Thread Series Designator:

Uns 1st mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0