NSN 5930-01-061-5878

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-061-5878

| View Online at https://aerobasegroup.com/nsn/5930-01-061-5878 |
|---|
| Thread Class: |
| 2b single mounting facility |
| Overall Length: |
| 5.031 inches |
| Overall Height: |
| 2.500 inches |
| First Flat Length: |
| 0.750 inches single actuator |
| Flat Height: |
| 0.219 inches single actuator |
| Shaft Diameter: |
| 0.250 inches single actuator |
| Shaft Length: |
| 1.000 inches single actuator |
| Individual Section Quantity: |
| 6 |
| Knob Manufacturer Code: |
| 82121 |
| Knob Manufacturer Part Number: |
| A |
| Knob Specificationial Markings: |
| Arrow |
| Longest Horizontal Distance Between Mounting Centers: |
| 1.641 inches single mounting facility |
| Longest Vertical Distance Between Mounting Centers: |
| 1.641 inches single mounting facility |
| Switch Contact Basic Design: |
| Nonpile-up symmetrical |
| Pole Quantity: |
| 1 each section rear |
| Throw Quantity: |
| 4 each section front |
| Mounting Method: |
| Bracket single mounting facility and threaded hole single mounting facility |
| Features Provided: |
| Actuator knob |
| Thready Qty Per Inch (tpi): |
| 24 single mounting facility |
| Thread Size: |
| 0.190 inches single mounting facility |

125.0 ac at sea level

Contact Voltage Rating In Volts:

NSN 5930-01-061-5878Rotary Switch - Page 2 of 2



| Rotor Through Connection Quantity: |
|---|
| 1 each section |
| Mounting Facility Pattern: |
| Four position rectangular single mounting facility |
| Switch Actuator Indexing Position Quantity: |
| 4 single actuator |
| Shaft Type: |
| Round, flatted, threaded hole single actuator |
| Criticality Code Justification: |
| Feat |
| Terminal Type: |
| Tab w/screw |
| Contact Switching Action: |
| Makes before breaks each section front |
| Switch Actuator Positioning Increment: |
| 90.0 degrees single actuator |
| Switch Actuator Stop Device Type: |
| Fixed stop single actuator |
| Contact Load Current Rating: |
| 10.0 amperes resistive load ac at sea level |
| Special Features: |
| tem must comply with requirements of desc production standard no. L02448; for navy nuclear propulsion plant products only |
| Style Designator: |
| Tap, circuit selector |
| Thread Series Designator: |
| Unc single mounting facility |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |
| No |
| Filg: |
| A052b0 |
| |
| |