

View Online at <https://aerobasegroup.com/nsn/5930-01-061-5886>

Thread Class:

2a single mounting facility

Thread Length:

0.437 inches single mounting facility

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

2.937 inches

First Flat Length:

0.250 inches single actuator

Flat Height:

0.216 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.437 inches single actuator

Overall Diameter:

Between 1.000 inches and 1.306 inches

Individual Section Quantity:

4

Nonturn Device Type:

Slotted bushing at 3: 00 o'clock

Operating Temperature Range:

-65.0/+125.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 each section front

Throw Quantity:

3 each section rear

Mounting Method:

Threaded bushing w/panel seal single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Flat/slot Angular Location:

195.0 degrees from nonturn device single actuator

Rotor Through Connection Quantity:

2 each section

Switch Actuator Indexing Position Quantity:

3 single actuator

Shaft Type:

Round, flatted single actuator

Criticality Code Justification:

Feat

Terminal Type:

Tab, solder lug

Contact Switching Action:

Makes before breaks each section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Detent Rotational Torque Range:

+1.000/+4.500 inch-pounds single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

75.0 milliamperes resistive load ac at sea level

Special Features:

Item must comply with requirements of desc production standard no. L02459; for navy nuclear propulsion plant products only

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0