

View Online at <https://aerobasegroup.com/nsn/5930-01-062-0606>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Dustproof

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.000 inches

**Body Length:**

1.940 inches

**Body Width:**

Between 0.677 inches and 0.697 inches

**Case Material:**

Plastic

**Unthreaded Mounting Hole Diameter:**

Between 0.139 inches and 0.142 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.940 inches

**Actuator Free Position Height:**

0.640 inches

**Maximum Voltage Rating In Volts:**

480.0 ac

**End Application:**

L.P.Compressors, mars class t-afs 1, forrestal class cv, oliver perry class ffg, whidbey island class lsd, iwo jima class lph, blue ridge class lcc-19, wichita class aor, cimmaron class ao.

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

10.0 ounces

**Criticality Code Justification:**

Feat

**Switch Actuating Force:**

Between 12.0 ounces and 20.0 ounces

**Actuator Movement:**

Between 0.007 pretravel inches and 0.010 overtravel inches and 0.002 differential inches and 0.003 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

20.000 amperes resistive ac

**Special Features:**

Weapon system essential

**Terminal Type And Quantity:**

3 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0