

View Online at <https://aerobasegroup.com/nsn/5930-01-062-0606>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches

Body Length:

1.940 inches

Body Width:

Between 0.677 inches and 0.697 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

Between 0.139 inches and 0.142 inches

Actuator Style:

Round

Actuator Diameter:

0.940 inches

Actuator Free Position Height:

0.640 inches

Maximum Voltage Rating In Volts:

480.0 ac

End Application:

L.P.Compressors, mars class t-afs 1, forrestal class cv, oliver perry class ffg, whidbey island class lsd, iwo jima class lph, blue ridge class lcc-19, wichita class aor, cimmaron class ao.

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

10.0 ounces

Criticality Code Justification:

Feat

Switch Actuating Force:

Between 12.0 ounces and 20.0 ounces

Actuator Movement:

Between 0.007 pretravel inches and 0.010 overtravel inches and 0.002 differential inches and 0.003 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

20.000 amperes resistive ac

Special Features:

Weapon system essential

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0