

View Online at <https://aerobasegroup.com/nsn/5930-01-062-2487>

Thread Class:

2a 2nd mounting facility

Thread Length:

0.469 inches 2nd mounting facility

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

5.250 inches

Overall Height:

2.810 inches

Overall Width:

2.810 inches

Shaft Length:

2.410 inches single actuator

Individual Section Quantity:

2

Knob Manufacturer Code:

82121

Knob Manufacturer Part Number:

A

Longest Horizontal Distance Between Mounting Centers:

2.297 inches 1st mounting facility

Longest Vertical Distance Between Mounting Centers:

2.297 inches 1st mounting facility

End Application:

MIs mk 25 mo 82121

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section periphery

Throw Quantity:

7 each section periphery

Mounting Method:

Threaded bushing 2nd mounting facility

Features Provided:

Actuator knob

Thready Qty Per Inch (tpi):

32 2nd mounting facility

Thread Size:

0.469 inches 2nd mounting facility

Contact Voltage Rating In Volts:

125.0 ac at sea level

Switch Actuator Momentary Position:

Counterclockwise single actuator

Mounting Facility Pattern:

Four position rectangular 1st mounting facility

Switch Actuator Indexing Position Quantity:

7 single actuator

Shaft Type:

Rectangular/square, threaded hole single actuator

Square Shaft Size:

0.250 inches single actuator

Terminal Type:

Screw

Contact Switching Action:

Breaks before makes each section periphery

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

10.0 amperes resistive load ac at sea level

Style Designator:

Tap, circuit selector

Thread Series Designator:

Uns 2nd mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0