## NSN 5930-01-062-4895

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-062-4895

**Thread Class:** 

2a single mounting facility

Thread Length:

0.469 inches single mounting facility

**Hazardous Locations/environmental Protection:** 

Dustproof

**Overall Length:** 

3.657 inches

First Flat Length:

1.438 inches single actuator

**Shaft Diameter:** 

0.250 inches single actuator

**Shaft Length:** 

1.657 inches single actuator

**Overall Diameter:** 

2.000 inches

**Individual Section Quantity:** 

......

**Knob Manufacturer Code:** 

82121

2

**Knob Manufacturer Part Number:** 

101605e-2a

**Knob Specificationial Markings:** 

White arrow

**Switch Contact Basic Design:** 

Nonpile-up symmetrical

Pole Quantity:

1 each section periphery

**Throw Quantity:** 

8 each section periphery

**Mounting Method:** 

Threaded bushing single mounting facility

Thready Qty Per Inch (tpi):

32 single mounting facility

**Thread Size:** 

0.469 inches single mounting facility

**Contact Voltage Rating In Volts:** 

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:** 

8 single actuator

**Shaft Type:** 

Round, parallel flatted single actuator

## NSN 5930-01-062-4895

Rotary Switch - Page 2 of 2



Terminal Type:
Tab w/screw
Contact Switching Action:
Breaks before makes each section periphery
Switch Actuator Positioning Increment:
45.0 degrees single actuator
Contact Load Current Rating:
5.0 amperes resistive load dc at sea level
Precious Material And Location:
Contact surfaces silver
Precious Material:
Silver
Style Designator:
Tap, circular, bushing mount
Thread Series Designator:
Uns single mounting facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A052b0