

View Online at <https://aerobasegroup.com/nsn/5930-01-062-4905>

Body Style:

Panel mount

Overall Length:

1.210 inches

Overall Height:

3.022 inches

Overall Width:

Between 0.950 inches and 0.970 inches

Body Length:

1.200 inches

Body Width:

Between 0.950 inches and 0.970 inches

Body Height:

2.812 inches

Case Material:

Metal

Actuator Length:

Between 1.020 inches and 1.050 inches

Actuator Style:

Rectangular

Actuator Height:

Between 0.164 inches and 0.210 inches

Actuator Width:

Between 0.720 inches and 0.750 inches

Actuator Color:

White single actuator

Illuminated Actuator Color:

Amber single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

End Application:

Gkilauea class t-ae 26, mars class t-afs 1, austin ship class lpd-4 amphibious transport docks. Spruance class dd (963), hayes class t-ag 195, oliver perry class ffg. Lm2500 machinery control systems.

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Nonpile-up Contact Arrangement:

4 pole, double throw, one position momentary single switch unit

Criticality Code Justification:

Feat

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac

Special Features:

Weapon systems essential. Features - full display lens with retainer clip.

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

12 turret and 5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0