

View Online at <https://aerobasegroup.com/nsn/5930-01-062-7388>

**Overall Length:**

3.500 inches

**Overall Width:**

2.813 inches

**Unthreaded Mounting Hole Diameter:**

0.195 inches

**Distance Between Mounting Facility Centers:**

1.750 inches

**Pressure Switch Type:**

Gage

**Mounting Method:**

Flange and unthreaded hole

**Features Provided:**

Tamper proof cap

**Thready Qty Per Inch (tpi):**

18 single pressure connection

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

200.00 pounds per square inch

**Thread Size:**

0.250 inches single pressure connection

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Screw

**Contact Load Current Rating:**

15.0 amperes resistive load single voltage

**Contact Adjustability:**

Deactuation point adjustable and actuation point adjustable

**Contact Adjustment Range:**

+10.00/+100.00 actuation point pounds per square inch and +10.00/+100.00 deactuation point pounds per square inch

**Contact Adjustment Type:**

Internal actuation point pointer with scale and internal deactuation point pointer with scale

**Contact Voltage Rating In Volts:**

250.0 ac at sea level single voltage

**Pressure Connector Type:**

Flareless, threaded external single connection

**Thread Series Designator:**

Npt single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0