

View Online at <https://aerobasegroup.com/nsn/5930-01-062-7388>

Overall Length:

3.500 inches

Overall Width:

2.813 inches

Unthreaded Mounting Hole Diameter:

0.195 inches

Distance Between Mounting Facility Centers:

1.750 inches

Pressure Switch Type:

Gage

Mounting Method:

Flange and unthreaded hole

Features Provided:

Tamper proof cap

Thready Qty Per Inch (tpi):

18 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

200.00 pounds per square inch

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

15.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+10.00/+100.00 actuation point pounds per square inch and +10.00/+100.00 deactuation point pounds per square inch

Contact Adjustment Type:

Internal actuation point pointer with scale and internal deactuation point pointer with scale

Contact Voltage Rating In Volts:

250.0 ac at sea level single voltage

Pressure Connector Type:

Flareless, threaded external single connection

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0