NSN 5930-01-062-7399

Sensitive Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-01-062-7399

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Oiltight and corrosion resistant
Actuator Length:
1.500 inches
Actuator Style:
Roller arm
Actuator Roller Diameter:
0.750 inches
Actuator Roller Width:
0.250 inches
Housing Height:
1.875 inches
Housing Length:
4.685 inches
Housing Width:
1.785 inches
Maximum Voltage Rating In Volts:
600.0 ac and 240.0 dc
Inclosure Type:
Fully enclosed
Nonpile-up Contact Arrangement:
2 two circuit, double break/double make, one position momentary single switch unit
Switch Actuating Force:
64.0 inch-ounces
Actuator Movement:
Between 18.0 pretravel degrees and 57.0 overtravel degrees and 10.0 differential degrees
Contact Load Current Rating At Maximum Rated Voltage:
400.000 milliamperes resistive dc and 150.000 milliamperes inductive dc and 600.000 milliamperes resistive ac
Terminal Type And Quantity:
8 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A053a0