NSN 5930-01-062-7402

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-062-7402

| Thread Class: |
|---|
| 2b |
| Body Style: |
| Bushing mounted |
| Overall Length: |
| 2.500 inches |
| Overall Height: |
| 0.625 inches |
| Overall Width: |
| 0.625 inches |
| Body Diameter: |
| 0.625 inches |
| Case Material: |
| Metal |
| Actuator Diameter: |
| 0.500 inches |
| Actuator Height: |
| 0.344 inches |
| Maximum Voltage Rating In Volts: |
| 125.0 ac and 30.0 dc |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Threaded bushing |
| Thready Qty Per Inch (tpi): |
| 32 |
| Thread Size: |
| 0.500 inches |
| Nonpile-up Contact Arrangement: |
| 2 two circuit, one position momentary single switch unit |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 3.000 amperes resistive dc and 3.000 amperes resistive ac |
| Precious Material And Location: |
| Contacts and terminals silver |
| Thread Series Designator: |
| Un |
| Terminal Type And Quantity: |
| 10 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 5930-01-062-7402

Push Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A053a0