NSN 5930-01-062-7906

Hazardous Locations/environmental Protection:

Push Switch - Page 1 of 2

Body Style:

Waterproof
Overall Height:
0.500 inches
Overall Width:
0.500 inches
Body Diameter:

Bushing mounted



View Online at https://aerobasegroup.com/nsn/5930-01-062-7906

0.562 inches
Bushing Length:
0.425 inches
Body Length:
1.040 inches
Case Material:
Metal
Actuator Length:
0.500 inches
Actuator Style:
Rectangular
Actuator Width:
0.500 inches
Actuator Color:
Black single actuator
Illuminated Actuator Color:
Green single actuator
Actuator Inscription:
Slew in single actuator
Maximum Voltage Rating In Volts:
1.5 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Threaded bushing
Thready Qty Per Inch (tpi):
32
Thread Size:
0.469 inches
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac and 3.000 amperes inductive ac

NSN 5930-01-062-7906

Push Switch - Page 2 of 2



Special Features:
White legend w/characters 0.087 in. H
Precious Material And Location:
Terminal surfaces gold
Thread Series Designator:
Uns
Terminal Type And Quantity:
3 turret and 2 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A053a0