NSN 5930-01-062-8556

Rotary Switch - Page 1 of 2

Thread Class:



View Online at https://aerobasegroup.com/nsn/5930-01-062-8556

2a single mounting facility Thread Length: 0.375 inches single mounting facility **Overall Length:** 2.088 inches **Overall Height:** 1.312 inches **Overall Width:** 1.280 inches First Flat Length: 0.312 inches single actuator Flat Height: 0.218 inches single actuator **Shaft Diameter:** 0.250 inches single actuator **Shaft Length:** 0.500 inches single actuator **Nonturn Device Radius:** 0.531 inches at 3: 00 o'clock **Individual Section Quantity:** 1 **Nonturn Device Type:** Tab at 3: 00 o'clock **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 2 single section front **Throw Quantity:** 4 single section rear **Mounting Method:** Threaded bushing single mounting facility **Thread Size:** 0.375 inches single mounting facility **Contact Voltage Rating In Volts:** 28.0 dc at sea level **Switch Actuator Indexing Position Quantity:** 4 single actuator **Shaft Type:** Round, flatted single actuator **Terminal Type:**

Tab, solder lug

NSN 5930-01-062-8556

Rotary Switch - Page 2 of 2



Conta	ct Sv	vitchin	a Act	ion:
oonta	10L 01	VILCIIII :	I ACL	IVII.

Breaks before makes single section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

1.0 amperes resistive load dc at sea level

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0