

View Online at <https://aerobasegroup.com/nsn/5930-01-063-1445>

**Thread Class:**

2a

**Body Style:**

Bushing mount

**Bushing Length:**

0.468 inches

**Body Length:**

0.414 inches

**Body Width:**

1.060 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.243 inches

**Actuator Height:**

0.687 inches

**Actuator Position-action Relationship:**

Up position maintained and down position maintained

**Maximum Voltage Rating In Volts:**

500.0 dc and 115.0 ac

**End Application:**

M60a3tts

**Mounting Surface To Terminal End Distance:**

1.020 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing w/panel seal

**Features Provided:**

Actuator seal and mounting hardware

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

1 pole, double throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

1.000 amperes resistive dc and 3.000 amperes resistive ac and 1.000 amperes inductive ac

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0