

View Online at <https://aerobasegroup.com/nsn/5930-01-063-1446>

Thread Class:

2a

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Driptight

Bushing Length:

0.468 inches

Body Length:

0.562 inches

Body Width:

0.354 inches

Body Height:

1.040 inches

Actuator Style:

Round

Actuator Diameter:

0.243 inches

Actuator Height:

0.687 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained

Actuator Position-locking Relationship:

Up position no locking action and down position no locking action

Maximum Voltage Rating In Volts:

50.0 dc and 115.0 ac

End Application:

M603tts

Mounting Surface To Terminal End Distance:

1.048 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing w/panel seal

Features Provided:

Mounting hardware

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 3.000 amperes resistive ac and 1.000 amperes inductive ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A053a0