

View Online at <https://aerobasegroup.com/nsn/5930-01-063-4479>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.470 inches single mounting facility

**Hazardous Locations/environmental Protection:**

Moisture resistant

**Overall Length:**

2.190 inches

**First Flat Length:**

0.400 inches single actuator and 0.447 inches single actuator

**Flat Height:**

0.182 inches single actuator and 0.223 inches single actuator

**Shaft Diameter:**

0.245 inches single actuator and 0.249 inches single actuator

**Shaft Length:**

0.530 inches single actuator

**Overall Diameter:**

1.810 inches

**Individual Section Quantity:**

1

**Nonturn Device Type:**

Slotted bushing at 6: 00 o'clock

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 single section periphery

**Throw Quantity:**

2 single section periphery

**Mounting Method:**

Threaded bushing single mounting facility

**Thready Qty Per Inch (tpi):**

32 single mounting facility

**Thread Size:**

0.469 inches single mounting facility

**Contact Voltage Rating In Volts:**

250.0 ac at sea level

**Shaft Flat/slot Angular Location:**

0.0 degrees from nonturn device single actuator

**Switch Actuator Indexing Position Quantity:**

2 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Screw

**Contact Switching Action:**

Makes before breaks single section periphery

**Switch Actuator Positioning Increment:**

45.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

2.0 amperes resistive load ac at sea level and 1.0 amperes inductive load ac at sea level and 1.5 amperes motor load ac at sea level

**Style Designator:**

Tap, circular, bushing mount

**Thread Series Designator:**

Uns single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0