

View Online at <https://aerobasegroup.com/nsn/5930-01-063-4479>

Thread Class:

2a single mounting facility

Thread Length:

0.470 inches single mounting facility

Hazardous Locations/environmental Protection:

Moisture resistant

Overall Length:

2.190 inches

First Flat Length:

0.400 inches single actuator and 0.447 inches single actuator

Flat Height:

0.182 inches single actuator and 0.223 inches single actuator

Shaft Diameter:

0.245 inches single actuator and 0.249 inches single actuator

Shaft Length:

0.530 inches single actuator

Overall Diameter:

1.810 inches

Individual Section Quantity:

1

Nonturn Device Type:

Slotted bushing at 6: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section periphery

Throw Quantity:

2 single section periphery

Mounting Method:

Threaded bushing single mounting facility

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.469 inches single mounting facility

Contact Voltage Rating In Volts:

250.0 ac at sea level

Shaft Flat/slot Angular Location:

0.0 degrees from nonturn device single actuator

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Screw

Contact Switching Action:

Makes before breaks single section periphery

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

2.0 amperes resistive load ac at sea level and 1.0 amperes inductive load ac at sea level and 1.5 amperes motor load ac at sea level

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Uns single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0