NSN 5930-01-063-7165

Push Switch - Page 1 of 2

Body Style:Panel mounted



View Online at https://aerobasegroup.com/nsn/5930-01-063-7165

| Overall Height: |
|--|
| 0.750 inches |
| Overall Width: |
| Between 1.350 inches and 1.460 inches |
| Body Width: |
| Between 1.350 inches and 1.460 inches |
| Body Height: |
| 0.740 inches |
| Actuator Length: |
| 0.740 inches |
| Actuator Style: |
| Rectangular |
| Actuator Height: |
| Between 0.164 inches and 0.210 inches |
| Actuator Width: |
| 0.740 inches |
| Actuator Color: |
| White single actuator |
| Illuminated Actuator Color: |
| Yellow single actuator and green single actuator |
| Actuator Inscription: |
| 2 single actuator |
| Maximum Voltage Rating In Volts: |
| 250.0 ac and 30.0 dc |
| Mounting Surface To Terminal End Distance: |
| 2.960 inches |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Panel |
| Features Provided: |
| Rfi shielding |
| Nonpile-up Contact Arrangement: |
| 2 pole, double throw, one position momentary single switch unit |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 5.000 amperes resistive dc and 2.500 amperes inductive dc and 5.000 amperes resistive ac |
| Precious Material And Location: |
| Contact and terminal surfaces gold |
| Terminal Type And Quantity: |
| 11 pin |
| |

NSN 5930-01-063-7165

Push Switch - Page 2 of 2



| C | ha | Ιf | 1 | ife | |
|---|-----|----|---|-------|--|
| • | ııe | | _ | .II C | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0