NSN 5930-01-063-9161

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-063-9161

5.250 inches

Overall Height:

5.719 inches

Overall Width:

1.875 inches

Mounting Slot Width:

0.250 inches

Body Height:

3.688 inches

Unthreaded Mounting Hole Diameter:

0.250 inches

Distance Between Mounting Facility Centers:

4.313 inches

Capillary Tube Length:

240.0 inches

Tempurature Sensing Element Type:

Capillary tube

Mounting Method:

Bracket and unthreaded hole and slot

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

7.2 amperes resistive load first voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+10.00/+90.00 actuation point degrees fahrenheit and +10.00/+90.00 deactuation point degrees fahrenheit

Contact Adjustment Type:

External deactuation point shaft with scale and external actuation point shaft with scale

Contact Voltage Rating In Volts:

277.0 ac at sea level first voltage

Frequency In Hertz:

50.0 second voltage and 60.0 second voltage

Media For Which Designed:

Gas or liquid

NSN 5930-01-063-9161

Thermostatic Switch - Page 2 of 2

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A048b0

