

View Online at <https://aerobasegroup.com/nsn/5930-01-063-9170>

Thread Class:

2a

Body Style:

Bushing mounted

Switch Actuator Quantity:

1

Actuator Style:

Roller plunger

Actuator Free Position Height:

Between 1.265 inches and 1.325 inches

Actuator Roller Diameter:

Between 0.370 inches and 0.380 inches

Actuator Roller Width:

Between 0.105 inches and 0.135 inches

Housing Diameter:

0.720 inches

Housing Length:

1.000 inches

Housing Bushing Length:

0.575 inches

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Switch Release Force:

64.0 ounces

Switch Actuating Force:

144.0 ounces

Actuator Movement:

Between 0.040 pretravel inches and 0.125 overtravel inches and 0.020 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes inductive dc

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0