NSN 5930-01-064-2445

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-064-2445

Thread Class:

2a single mounting facility

Thread Length:

0.438 inches single mounting facility

Overall Length:

2.856 inches

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

1.750 inches single actuator

Individual Section Quantity:

1

End Application:

Strategic weapon systems (poseidon and trident).

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section rear

Throw Quantity:

1 single section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Round single actuator

Criticality Code Justification:

Feat

Terminal Type:

Tab, solder lug

Contact Switching Action:

Makes before breaks single section rear

Switch Actuator Positioning Increment:

60.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

500.0 milliamperes resistive load ac at sea level

NSN 5930-01-064-2445Rotary Switch - Page 2 of 2



Special Features:
Weapon system essential
Precious Material And Location:
Contacts and rotor surfaces silver
Precious Material:
Silver
Style Designator:
Circular wafer, bushing mount
Thread Series Designator:
Unef single mounting facility
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No Fiig: A052b0