

View Online at <https://aerobasegroup.com/nsn/5930-01-064-3836>

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.875 inches

**Body Length:**

1.094 inches

**Body Width:**

0.400 inches

**Body Height:**

0.625 inches

**Unthreaded Mounting Hole Diameter:**

0.114 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

0.406 inches

**Actuator Length:**

0.110 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

0.114 inches

**Actuator Width:**

0.165 inches

**Actuator Free Position Height:**

0.625 inches

**Maximum Voltage Rating In Volts:**

125.0 ac and 250.0 dc

**Inclosure Type:**

Fully enclosed

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Actuating Force:**

0.5 grams

**Actuator Movement:**

Between 0.047 pretravel inches and 0.050 overtravel inches and 0.010 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

250.000 milliamperes resistive dc and 3.000 amperes lamp ac

**Terminal Type And Quantity:**

3 quick disconnect, male

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A053a0