NSN 5930-01-064-4148

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-064-4148 **Thread Class:** 2a single mounting facility Thread Length: 0.375 inches single mounting facility **Overall Length:** 1.353 inches **Overall Height:** 1.468 inches **Overall Width:** 1.312 inches **Shaft Diameter:** 0.250 inches single actuator **Shaft Length:** 0.093 inches single actuator **Nonturn Device Radius:** 0.437 inches at 9: 00 o'clock **Individual Section Quantity:** 1 **Nonturn Device Type:** Tab at 9: 00 o'clock **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 1 single section rear **Throw Quantity:** 11 single section rear **Mounting Method:** Threaded bushing single mounting facility **Thread Size:** 0.375 inches single mounting facility **Contact Voltage Rating In Volts:** 28.0 dc at sea level **Switch Actuator Indexing Position Quantity:** 12 single actuator **Shaft Type:** Round single actuator **Terminal Type:** Tab, solder lug **Contact Switching Action:** Breaks before makes single section rear **Switch Actuator Positioning Increment:**

30.0 degrees single actuator

NSN 5930-01-064-4148

Rotary Switch - Page 2 of 2



Co	ntact	l oad	Current	Rating:
vu	ıııacı	. Luau	Current	mauniu.

1.5 amperes resistive load dc at sea level

Precious Material And Location:

Clip and rotor contact surfaces silver

Precious Material:

Silver

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0