

View Online at <https://aerobasegroup.com/nsn/5930-01-064-9006>

Thread Length:

0.650 inches single pressure connection

Overall Length:

2.500 inches

Outside Diameter:

0.250 inches single connection

Body Length:

1.090 inches

Overall Diameter:

0.870 inches

Pressure Switch Type:

Gage

Width Across Flats:

0.750 inches

Operating Temperature Rating:

Between -30.0 degrees fahrenheit and 160.0 degrees fahrenheit

Mounting Method:

Inlet connection

Contact Action Stimulus:

Increase

Proof Pressure:

300.00 pounds per square inch

Thread Size:

0.250 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Wire lead

Contact Load Current Rating:

7.0 amperes resistive load second voltage 7.0 amperes resistive load third voltage 7.0 amperes resistive load first voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+20.00/+75.00 actuation point pounds per square inch and +15.00/+70.00 deactuation point pounds per square inch

Contact Adjustment Type:

External deactuation point serrated nut and external actuation point serrated nut

Contact Voltage Rating In Volts:

115.0 ac at sea level first voltage 28.0 dc at sea level third voltage 230.0 ac at sea level second voltage

Pressure Connector Type:

Inverted flare, threaded external single connection

Frequency In Hertz:

50.0 first voltage and 60.0 first voltage 50.0 second voltage and 60.0 second voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0