NSN 5930-01-064-9947

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-064-9947 **Overall Length: 5.188** inches **Overall Height:** 5.250 inches **Overall Width:** 2.812 inches **Body Height:** 2.750 inches **Unthreaded Mounting Hole Diameter:** 0.281 inches **Capillary Tube Length:** 120.0 inches **Bulb Length:** 3.625 inches **Bulb Diameter:** 0.688 inches **Longest Horizontal Distance Between Mounting Centers:** 2.406 inches **Intermediate Horizontal Distance Between Mounting Centers:** 0.656 inches **Longest Vertical Distance Between Mounting Centers:** 3.281 inches **End Application:** Compressor 28953 **Tempurature Sensing Element Type:** Capillary tube-bulb **Operating Tempurature Rating:** 500.0 degrees fahrenheit **Mounting Method:** Bracket and unthreaded hole **Features Provided:** Electrical access port **Contact Action Stimulus:** Increase **Mounting Facility Pattern:** Obtuse triangle **Nonpile-up Contact Arrangement:** 1 pole, single throw, normally open, momentary action **Terminal Type:**

Tab w/screw

Contact Load Current Rating:

9.6 amperes inductive load fourth voltage

NSN 5930-01-064-9947

Thermostatic Switch - Page 2 of 2



Contact	Adi	ustab	ility:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+377.00/+485.00 actuation point degrees fahrenheit and +375.00/+480.00 deactuation point degrees fahrenheit

Contact Adjustment Type:

Internal deactuation point screw and internal actuation point screw

Contact Voltage Rating In Volts:

550.0 dc at sea level third voltage

Media For Which Designed:

Gas

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A048b0