

View Online at <https://aerobasegroup.com/nsn/5930-01-064-9953>

Body Style:

Bushing mount

Bushing Length:

0.470 inches

Body Length:

1.100 inches

Body Width:

0.670 inches

Actuator Style:

Round

Actuator Diameter:

0.430 inches

Actuator Height:

1.180 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained and center position maintained

Actuator Position-locking Relationship:

Up position no locking action and down position locked in and center position no locking action

Actuator Color:

White single actuator

Maximum Voltage Rating In Volts:

250.0 ac and 400.0 dc

Inclosure Type:

Uninclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

4 pole, double throw, two positions momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 7.000 amperes inductive dc and 3.300 amperes motor dc and 2.000 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 3.300 amperes motor ac and 2.000 amperes lamp ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

12 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0