

View Online at <https://aerobasegroup.com/nsn/5930-01-064-9953>

**Body Style:**

Bushing mount

**Bushing Length:**

0.470 inches

**Body Length:**

1.100 inches

**Body Width:**

0.670 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.430 inches

**Actuator Height:**

1.180 inches

**Actuator Position-action Relationship:**

Up position maintained and down position maintained and center position maintained

**Actuator Position-locking Relationship:**

Up position no locking action and down position locked in and center position no locking action

**Actuator Color:**

White single actuator

**Maximum Voltage Rating In Volts:**

250.0 ac and 400.0 dc

**Inclosure Type:**

Uninclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

4 pole, double throw, two positions momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

7.000 amperes resistive dc and 7.000 amperes inductive dc and 3.300 amperes motor dc and 2.000 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 3.300 amperes motor ac and 2.000 amperes lamp ac

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

12 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0